



Kombimechaniken



Angaben in mm

Art.-Nr.	Stück / Karton	Füllhöhe	ges. Höhe	ges. Breite	Gehäusebreite	ges. Länge	Nietlochabstand	Ringabstände	Drahtbügel - Ø	kg / Karton
D 120 02 13 (15)	1.000	13,5	23,0	19,5	15,0	120	112,0	80	1,8 x 2,55	16,4
D 123 02 16 (17)	800	16,0	25,5	23,0	17,0	123	114,0	80	1,8 x 3,0	15,1
D 123 02 16 (20)	800	16,5	27,0	23,5	20,0	123	114,0	80	2,2 x 3,4	19,0
D 123 02 20 (20)	500	20,0	32,0	27,0	20,0	123	114,0	80	2,2 x 3,4	12,6
D 123 02 25 (20)	500	25,0	36,0	29,5	20,0	123	114,0	80	2,2 x 3,4	14,8
D 123 02 30 (20)	400	28,0	39,5	30,0	20,0	123	114,0	80	2,2 x 3,4	12,1
D 123 02 30 (26)	400	30,0	42,5	35,0	26,0	124	114,0	80	2,5 x 4,0	17,0
D 123 02 35 (26)	400	33,0	44,5	36,0	26,0	124	114,0	80	2,5 x 4,0	17,6
D 123 02 40 (26)	320	40,0	52,5	40,0	26,0	124	114,0	80	2,5 x 4,0	15,3
D 123 02 45 (26)	240	45,0	58,0	44,0	26,0	124	114,0	80	3,0 x 4,5	14,3
D 123 02 50 (26)	240	52,0	65,5	42,5	26,0	124	114,0	80	3,0 x 4,5	15,2
D 136 02 55 (36)	180	54,0	71,0	55,5	36,0	133	124,0	80	3,2 x 4,8	17,7
D 136 02 60 (36)	180	58,0	75,5	55,5	36,0	133	124,0	80	3,8 x 5,5	20,2
D 136 02 65 (36)	180	65,0	82,0	61,0	36,0	133	124,0	80	3,9 x 5,5	21,6
D 210 04 16 (20)	300	16,5	27,0	23,5	20,0	210	200,0	45 - 65 - 45	2,2 x 3,4	13,7
D 210 04 20 (20)	300	20,0	32,0	27,0	20,0	210	200,0	45 - 65 - 45	2,2 x 3,4	15,0
D 210 04 25 (20)	250	25,0	36,0	29,5	20,0	210	200,0	45 - 65 - 45	2,2 x 3,4	13,1
D 210 04 30 (26)	200	30,0	43,0	36,0	26,0	209	200,0	45 - 65 - 45	3,0 x 4,5	15,2
D 210 04 36 (26)	200	36,0	47,0	39,0	26,0	209	200,0	45 - 65 - 45	2,5 x 4,0	16,2
D 210 04 40 (26)	200	40,0	53,0	41,0	26,0	209	200,0	45 - 65 - 45	2,5 x 4,0	17,0
D 210 04 45 (26)	160	45,0	58,0	44,0	26,0	209	200,0	45 - 65 - 45	3,0 x 4,5	18,0
A D 210 04 50 (29)	120	50,0	62,0	48,5	29,0	209	200,0	45 - 65 - 45	3,0 x 4,5	14,9
N D 210 04 50 (26)	120	52,0	65,5	42,5	26,0	209	200,0	45 - 65 - 45	3,0 x 4,5	14,2
D 216 04 55 (36)	90	54,0	71,0	55,5	36,0	209	200,0	45 - 65 - 45	3,2 x 4,8	18,0
D 216 04 65 (36)	90	65,0	82,0	61,0	36,0	209	200,0	45 - 65 - 45	3,8 x 5,5	20,2

A = Auslaufmodell (Verkauf solange wie Bestand vorhanden ist)











N = Nachfolgemodell (Kann erst geliefert werden, wenn Auslaufmodell vergriffen ist)



Kombimechaniken

Angaben in mm



Art.-Nr.	 Stück / Karton	 Füllhöhe	 ges. Höhe	 ges. Breite	 Gehäusebreite	 ges. Länge	 Nietlochabstand	 Ringabstände	 Drahtbügel - Ø	 kg / Karton
D 282 04 13 (17)	300	13,0	22,0	20,0	17,0	282	272,5	80 - 80 - 80	1,8 x 2,55	15,4
D 282 04 16 (17)	400	17,0	26,5	23,0	17,0	282	272,5	80 - 80 - 80	1,8 x 2,93	20,5
D 287 04 20 (20)	250	20,0	32,0	27,0	20,0	286	277,0	80 - 80 - 80	2,2 x 3,4	16,9
D 287 04 25 (20)	250	25,0	36,0	29,5	20,0	286	277,0	80 - 80 - 80	2,2 x 3,4	17,4
D 287 04 30 (26)	160	30,0	42,5	35,0	26,0	286	277,0	80 - 80 - 80	2,5 x 4,0	16,1
D 287 04 35 (26)	160	33,0	44,5	36,0	26,0	286	277,0	80 - 80 - 80	2,5 x 4,0	17,0
D 287 04 40 (26)	160	40,0	52,5	40,0	26,0	286	277,0	80 - 80 - 80	2,5 x 4,0	18,7
D 287 04 45 (26)#	120	45,0	58,0	44,0	26,0	286	277,0	80 - 80 - 80	3,0 x 4,5	15,8
D 287 04 50 (26)#	120	52,0	65,5	42,5	26,0	286	277,0	80 - 80 - 80	3,0 x 4,5	17,5
D 300 04 55 (36)#	60	54,0	71,0	55,5	36,0	299	290,0	80 - 80 - 80	3,2 x 4,8	12,9
D 300 04 60 (36)#	60	58,0	75,5	55,5	36,0	299	290,0	80 - 80 - 80	3,8 x 5,5	15,2
D 300 04 65 (36)#	60	65,0	82,0	61,0	36,0	299	290,0	80 - 80 - 80	3,8 x 5,5	16,0