













Bügelmechaniken

Angaben in mm



Art.-Nr.	 Stück / Karton	 Füllhöhe	 ges. Höhe	 ges. Breite	 Gehäusebreite	 ges. Länge	 Nietlochabstand	 Ringabstände	 Drahtbügel - Ø	 kg / Karton
Q 123 02 20 (20)	500	20,0	31,5	24,5	20,0	123	114,0	80	2,2 x 3,4	12,6
Q 123 02 25 (20)	500	25,0	36,0	25,0	20,0	123	114,0	80	2,2 x 3,4	14,0
Q 123 02 30 (26)	300	30,0	42,5	30,5	26,0	124	114,0	80	3,0 x 4,5	12,6
Q 123 02 35 (26)	320	35,0	47,5	30,5	26,0	124	114,0	80	3,0 x 4,5	13,7
Q 123 02 40 (26)	320	41,0	54,0	31,5	26,0	124	114,0	80	3,0 x 4,5	15,8
Q 123 02 45 (26)	400	43,0	56,0	33,0	26,0	124	114,0	80	3,0 x 4,5	22,3
Q 136 02 65 (36)	180	65,0	82,0	43,0	36,0	133	124,0	80	3,8 x 5,5	21,0
Q 136 02 80 (36)	120	80,0	97,0	39,5	36,0	133	124,0	80	3,8 x 5,5	16,3
Q 287 04 20 (20)	250	20,0	31,5	24,5	20,0	286	277,0	80-80-80	2,2 x 3,4	18,0
Q 287 04 25 (20)	250	25,0	36,0	25,0	20,0	286	277,0	80-80-80	2,2 x 3,4	18,8
Q 287 04 30 (26)	160	30,0	42,5	30,5	26,0	286	277,0	80-80-80	3,0 x 4,5	15,7
Q 287 04 35 (26)	160	35,0	47,5	30,5	26,0	286	277,0	80-80-80	3,0 x 4,5	17,3
Q 287 04 40 (26)	160	41,0	54,0	31,5	26,0	286	277,0	80-80-80	3,0 x 4,5	18,1
Q 287 04 45 (26)#	120	43,0	56,0	33,0	26,0	286	277,0	80-80-80	3,0 x 4,5	16,1
A Q 287 04 50 (29)#	120	50,0	62,0	36,0	29,0	287	277,0	80-80-80	3,0 x 4,5	19,2
Q 300 04 65 (36)#	60	65,0	82,0	43,0	36,0	299	290,0	80-80-80	3,8 x 5,5	15,8
Q 300 04 80 (36)#	60	80,0	97,0	39,5	36,0	299	290,0	80-80-80	3,8 x 5,5	17,5

= drittes Nietloch

A = Auslaufmodell (Verkauf solange wie Bestand vorhanden ist)